

SV680 범용 서보드라이브

Born for High-End Market



● 펄스/아날로그 지령

CANopen

EtherCAT



SPECIFICATIONS

Single-phase 220 V servo drive

Item	Size-A		Size-C		Size-D
Drive model SV680P	S1R6	S2R8	S5R5	S7R6	S012
Continuous output current (Arms)	1.6	2.8	5.5	7.6	12
Maximum output current (Arms)	5.8	10.1	16.9	23	32
Main circuit power supply	Single-phase 200–240 VAC, –10% to +10%, 50/60 Hz				
Control circuit power supply	Single-phase 200–240 VAC, –10% to +10%, 50/60 Hz				
Braking capability	Built-in and external braking resistors are supported by the whole SV680 family except servo drives in size A, which support external braking resistors only.				

Three-phase 220 V servo drive

Item	Size-A		Size-C		Size-D		Size-E	
Drive model SV680P	S1R6	S2R8	S5R5	S7R6	S012	S018	S022	S027
Continuous output current (Arms)	1.6	2.8	5.5	7.6	12	18	22	27
Maximum output current (Arms)	5.8	10.1	16.9	23	32	45	55	67.5
Main circuit power supply	Three-phase 200–240 VAC, –10% to +10%, 50/60 Hz							
Control circuit power supply	Three-phase 200–240 VAC, –10% to +10%, 50/60 Hz							
Braking capability	Built - in and external braking resistors are supported by the whole SV680 family except servo drives in size A, which support external braking resistors only.				Built - in braking resistor by default, external braking resistor supported			


Three-phase 380 V servo drive

Item	Size-C		Size-D		Size-E		
Drive model SV680P	T3R5	T5R4	T8R4	T012	T017	T021	T026
Continuous output current (Arms)	3.5	5.4	8.4	12	17	21	26
Maximum output current (Arms)	11	14	20	30	42.5	52.5	65
Main circuit power supply	Three-phase 380–480 VAC, –10% to +10%, 50/60 Hz						
Control circuit power supply	Single-phase 380–480 VAC, –10% to +10%, 50/60 Hz						
Braking capability	Built-in braking resistor						


Note: The power of the full SV680 series is in the range of 0.05 kW to 7.5 kW. The power of the models released before February 2022 is 1 kW or below.

DIMENSIONS

SV680N Series



SV680P Series



Structure	L mm(in.)	H mm(in.)	D mm(in.)	L1 mm(in.)	H1 mm(in.)	D1 mm(in.)	Screw Hole (ØLA)	Tightening Torque (N·m)	Weight (kg)
SIZE A	45.5 (1.79)	170 (6.69)	150 (5.91)	33 (1.10)	161 (6.34)	75 (2.95)	2-M4	1.2	0.96
SIZE B	55±1 (2.17±0.04)	170 (6.69)	173±1 (6.81±0.04)	44 (1.37)	160 (6.30)	75 (2.95)	2-M4	1.2	1.3
SIZE C	80±1 (3.15±0.04)	170 (6.69)	183 (7.20)	71 (2.80)	160 (6.30)	75 (2.95)	3-M4	1.2	1.8
SIZE D	90 (3.54)	250 (9.84)	230 (9.06)	78 (3.07)	241 (9.47)	75 (2.95)	4-M4	1.2	3.6

SELECTION CHART

Item	Model	Appearance	Servo Drive Model	Applicable motor power	Applicable motor model
Single-phase 200 V models	Size A		SV680*S1R6I-GINT	 50W 100W 200W	MS1H1-05B30CB-A63*R-INT MS1H1-10B30CB-A63*R-INT MS1H1-20B30CB-A63*R-INT MS1H4-05B30CB-A63*R-INT MS1H4-10B30CB-A63*R-INT MS1H4-20B30CB-A63*R-INT MS1H1-20B30CB-V63*R-INT MS1H4-20B30CB-V63*R-INT
			SV680*S2R8I-GINT	 400W	MS1H1-40B30CB-A63*R-INT MS1H4-40B30CB-A63*R-INT MS1H1-40B30CB-V63*R-INT MS1H4-40B30CB-V63*R-INT
	Size C		SV680*S5R5I-GINT	 550W 750W	MS1H1-55B30CB-A630R-INT MS1H1-75B30CB-A63*R-INT MS1H4-55B30CB-A630R-INT MS1H4-75B30CB-A63*R-INT MS1H1-55B30CB-V63*R-INT MS1H1-75B30CB-V63*R-INT MS1H4-55B30CB-V63*R-INT MS1H4-75B30CB-V63*R-INT
			SV680*S7R6I-GINT	 850W 1KW	MS1H1-10C30CB-A63*R-INT MS1H2-10C30CB-A63*R-INT MS1H3-85B15CB-A63*R-INT MS1H4-10C30CB-A63*R-INT MS1H1-10C30CB-V63*R-INT MS1H2-10C30CB-V63*R-INT MS1H3-85B15CB-V63*R-INT MS1H4-10C30CB-V63*R-INT
	Size D		SV680*S012I-GINT	 1.3KW 1.5KW	MS1H2-15C30CB-A63*R-INT MS1H3-13C15CB-A63*R-INT MS1H2-15C30CB-V63*R-INT MS1H3-13C15CB-V63*R-INT

SELECTION CHART

Item	Model	Appearance	Servo Drive Model	Applicable motor power	Applicable motor model	
Three-phase 200 V models	Size A		SV680*S1R6I-GINT	 50W 100W 200W	MS1H1-05B30CB-A63*R-INT MS1H1-10B30CB-A63*R-INT MS1H1-20B30CB-A63*R-INT MS1H4-05B30CB-A63*R-INT MS1H4-10B30CB-A63*R-INT MS1H4-20B30CB-A63*R-INT	MS1H1-20B30CB-V63*R-INT MS1H4-20B30CB-V63*R-INT
			SV680*S2R8I-GINT	 400W	MS1H1-40B30CB-A63*R-INT MS1H4-40B30CB-A63*R-INT	MS1H1-40B30CB-V63*R-INT MS1H4-40B30CB-V63*R-INT
	Size C		SV680*S5R5I-GINT	 550W 750W	MS1H1-55B30CB-A630R-INT MS1H1-75B30CB-A63*R-INT MS1H4-55B30CB-A630R-INT MS1H4-75B30CB-A63*R-INT	MS1H1-55B30CB-V63*R-INT MS1H1-75B30CB-V63*R-INT MS1H4-55B30CB-V63*R-INT MS1H4-75B30CB-V63*R-INT
			SV680*S7R6I-GINT	 850W 1KW	MS1H1-10C30CB-A63*R-INT MS1H2-10C30CB-A63*R-INT MS1H3-85B15CB-A63*R-INT MS1H4-10C30CB-A63*R-INT	MS1H1-10C30CB-V63*R-INT MS1H2-10C30CB-V63*R-INT MS1H3-85B15CB-V63*R-INT MS1H4-10C30CB-V63*R-INT
	Size D		SV680*S012I-GINT	 1.3KW 1.5KW	MS1H2-15C30CB-A63*R-INT MS1H3-13C15CB-A63*R-INT	MS1H2-15C30CB-V63*R-INT MS1H3-13C15CB-V63*R-INT
	Size E		SV680*S018I-GINT	 1.8KW 2KW	MS1H2-20C30CB-A63*R-INT MS1H3-18C15CB-A63*R-INT	MS1H2-20C30CB-V63*R-INT MS1H3-18C15CB-V63*R-INT
			SV680*S022I-GINT	 2.5KW 2.9KW 3KW	MS1H2-25C30CB-A63*R-INT MS1H2-30C30CB-A63*R-INT MS1H3-29C15CB-A63*R-INT	MS1H2-25C30CB-V63*R-INT MS1H2-30C30CB-V63*R-INT MS1H3-29C15CB-V63*R-INT
			SV680*S027I-GINT	 4KW 4.4KW 5KW	MS1H2-40C30CB-A63*R-INT MS1H2-50C30CB-A63*R-INT MS1H3-44C15CB-A63*R-INT	MS1H2-40C30CB-V63*R-INT MS1H2-50C30CB-V63*R-INT MS1H3-44C15CB-V63*R-INT

SELECTION CHART

Item	Model	Appearance	Servo Drive Model	Applicable motor power	Applicable motor model	
Threephase 400V models	Size C		SV680*T3R5I-GINT	 850W 1KW	MS1H2-10C30CD-A63*R-INT MS1H3-85B15CD-A63*R-INT	MS1H2-10C30CD-V63*R-INT MS1H3-85B15CD-V63*R-INT
			SV680*T5R4I-GINT	 1.3KW 1.5KW	MS1H2-15C30CD-A63*R-INT MS1H3-13C15CD-A63*R-INT	MS1H2-15C30CD-V63*R-INT MS1H3-13C15CD-V63*R-INT
	Size D		SV680*T8R4I-GINT	 1.8KW 2KW 2.5KW	MS1H2-20C30CD-A63*R-INT MS1H2-25C30CD-A63*R-INT MS1H3-18C15CD-A63*R-INT	MS1H2-20C30CD-V63*R-INT MS1H2-25C30CD-V63*R-INT MS1H3-18C15CD-V63*R-INT
			SV680*T012I-GINT	 2.9KW 3KW	MS1H2-30C30CD-A63*R-INT MS1H3-29C15CD-A63*R-INT	MS1H2-30C30CD-V63*R-INT MS1H3-29C15CD-V63*R-INT
	Size E		SV680*T017I-GINT	 4KW 4.4KW	MS1H2-40C30CD-A63*R-INT MS1H3-44C15CD-A63*R-INT	MS1H2-40C30CD-V63*R-INT MS1H3-44C15CD-V63*R-INT
			SV680*T021I-GINT	 5KW 5.5KW	MS1H2-50C30CD-A63*R-INT MS1H3-55C15CD-A63*R-INT	MS1H2-50C30CD-V63*R-INT MS1H3-55C15CD-V63*R-INT
			SV680*T026I-GINT	 7.5KW	MS1H3-75C15CD-A63*R-INT	MS1H3-75C15CD-V63*R-INT

[1] The expansion functional safety module is not included in standard models.

NOTE

[illegible]

Driven by technology

AC drives



AC MultiDrives



MV drives



Single-Axis servos



Multi-Axis servos



Robotics & motion controllers



PLCs & HMIs



CNC machine tool solutions



Electric vehicle inverters



International Offices



Germany-Stuttgart

Tel: +49 (0) 7144 8990 | sales.de@inovance.eu



Italy-Milano

Tel: +39 (0) 2268 22318 | sales.it@inovance.eu



France-Bordeaux

Tel: +33 (0) 5594 01050 | sales.fr@inovance.eu



Turkey-Istanbul

Tel: +90 (216) 706 17 89 | info@inovance.eu



Spain-Barcelona

Tel: +34 93 504 94 48 | sales.es@inovance.eu



Hong Kong SAR

Tel: +852 2751 6080 | info@inovance.eu



India

Head Office Chennai | Tel: +91 (0) 44 4380 0201

Ahmedabad | Tel: +91 794003 4272

Mumbai | Tel: +91 22 4971 5883

New Delhi | Tel: +91 11 4165 4524

Sales Network

in Kolkata, Bengaluru, Pune, Coimbatore,

Hyderabad, Vadodara, Jaipur

Email: info@inovance.ind.in

SOUTH KOREA

Office Tel: +82 (0)2 3489 8850
info@inovance.eu

For other country distributors,
contact the Hong Kong office.

Inovance Technology Companies
Shenzhen Inovance Technology Co. Ltd.
Suzhou Inovance Technology Co. Ltd.

INOVANCE
www.inovance.eu